

	Standard	Result
 Size		1219,2mm x 177,8mm
 Thickness		3,0mm
 Wear layer		0,55mm
 Surface treatment		K-Guard+ PU coating
 Guarantee	Light Industrial Commercial Domestic	10 Years 12 Years 15 Years
 Bevelled edge		No
 Standards	EN 649	Heterogeneous PVC
 Classification	EN 685- Light Industrial EN 685- Commercial EN 685- Domestic	42: Light Industrial general 33: Commercial heavy 23: Domestic heavy
 Reaction to fire	EN 13501-1 ISO 9239-1 ISO 11925-2	B ₁ -s1 Pass Pass
 Slip resistance	EN 13893 DIN 51130 DIN 51097	D5 R10 Class B
 Staining resistance	EN 423	Class 0
 Light fastness	ISO 105-B02	≥ 7
 Abrasion resistance	EN 660-2	Group T
 Mass surface	EN 430	5044g/m ²
 Dimensional stability	EN 434	≤ 0,25%
 Acoustic impact noise reduction	EN ISO 717-2 EN ISO 140-8	ΔL _w = 4 dB
 Electrical behaviour body voltage	EN 1815	Pass
 Indentation - residual	EN 433	≤ 0,1mm
 Castor chair continuous use	EN 425	Pass
 Thermal conductivity	ISO 8302	0,0147m ² K/W Suitable for underfloor heating (max 27°C)
 VOC emission	NF EN ISO 1600 DIBt / AgBB	A+ <250µg/m ³ Pass
 Adhesive	Universal Acrylic Epoxy High Temperature Pressure Sensitive	Yes Yes Yes Yes Yes
 Recycling		Suitable



Designflooring
T: +44 (0)1386 820105
F: +44 (0)1386 820132

Designflooring SAS
T: 01 57 32 39 13
F: 01 57 32 39 14

Designflooring GmbH
T: 0211 469 59203
F: 0211 469 59204

Designflooring Nederland
T: 020 200 8282
F: 020 200 8386

e: info@designflooring.com
www.designflooring.com

DFVANGSWBK2.2 | KD1925DF1

Van Gogh