


Technical specification

	Standard	Result
 Size		Plank 1220,0mm x 179,0mm Tile 600,0mm x 307,0mm
Thickness		4,5mm
Wear layer		0,4mm
Surface treatment		K-Guard+ PU coating
Guarantee	Light industrial Commercial Domestic	12 years 12 years Lifetime warranty
Bevelled edge		No
Standards	EN 649	Heterogeneous PVC
Classification	EN 685- Light industrial EN 685- Commercial EN 685- Domestic	41: Light industrial moderate 32: Commercial general 23: Domestic heavy
Reaction to fire	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Bfl-s1 Pass Pass
Staining resistance	EN 423	Class 0
Light fastness	EN ISO 105-B02	≥7
Abrasion resistance	EN 660-2	Group T
Dimensional stability	EN 434	≤ 0,15%
Acoustic impact noise reduction	EN ISO 717-2 EN ISO 140-8	$\Delta L_W = 4$ dB
Electrical behaviour body voltage	EN 1815	Pass
Indentation - residual	EN 433	≤ 0,1mm
Castor chair continuous use	EN 425	Pass
Mass per unit area	EN430	8,454 g/m ²
Thermal conductivity	ISO 8302	0,0197 m ² K/W Suitable for underfloor heating. Max 27°C
Slip resistance	DIN 51130 DIN 51097 EN 13893	R10 Plank B, Tile C DS
VOC emission	NF EN ISO 1600 DIBt/AgBB	A+ (<250µg/m ²) Pass
Adhesive	None required; please install according to our installation instructions.	
Recycling		Suitable

Palio Clic by Designflooring uses a patented L2C locking mechanism

