



CONSTRUCTION	Tufting 1/10" saxony
STRUCTURE	Tufté 1/10" saxony
STRUKTUR	Getuftet 1/10" Saxony
STRUCTUUR	Getuft 1/10" saxony
PILE MATERIAL	100% PA 6 IMPREL®
COMPOSITION DU VELOURS	
POLMATERIAL	
POOLMATERIAAL	
PRIMARY BACKING	Non woven PES
SUPPORT	Non woven PES
TRÄGERMATERIAL	Vlies PES
TUFTDOEK	Non woven PES
SECONDARY BACKING	Action Back
DOSSIER	
RÜCKEN	
TAPIJTRUG	
PILE WEIGHT	Ca. 1.150 gr/m ²
POIDS DU VELOURS	
POLEINSATZGEWICHT	
POOLGEWICHT	
TOTAL WEIGHT	Ca. 2.020 gr/m ²
POIDS TOTAL	
GESAMTGEWICHT	
TOTAAL GEWICHT	
PILE HEIGHT	Ca. 5 mm
EPAISSEUR DU VELOURS	
POLHÖHE	
POOLHOOGTE	
TOTAL HEIGHT	Ca. 8 mm
EPAISSEUR TOTALE	
GESAMTHÖHE	
TOTALE DIKTE	
TUFT DENSITY	Ca. 209 000/m ²
NOMBRES DE POINTS	
NOPPENZAHL	
AANTAL PUNTEN	
PILE DENSITY	Ca. 0.153 g/cm ³
DENSITÉ DU VELOURS	
POLROHDICHTÉ	
POOLDICHTHEID	
CLASSIFICATION	EN 1307
CLASSEMENT	33 - LC4
KLASSIFIKATION	
CLASSIFICATIE	
UPEC	U3s P3 E1 C0 (col. 33/38 = U3 P3) Certification CSTB:11/286
CASTOR CHAIR SUITABILITY	EN 985
CHAISE À ROULETTES	A: intensive use
STUHLROLLENEIGNUNG	
ROLSTOELGESCHIKTHEID	
STAIR SUITABILITY	EN 1963
ESCALIERS	A: intensive use
TREPPENEIGNUNG	
TRAPPENGESCHIKTHEID	


PERMANENTLY ANTISTATIC	ISO 6356
ANTISTATIQUE PERMANENT	< 2 kV
PERMANENT ANTISTATISCH	
PERMANENT ANTISTATISCH	
IMPACT NOISE RATING	ISO 140-8
ISOLATION PHONIQUE	26 dB ΔLw
TRITTSCHALLVERBESSERUNG	
GELUIDSISOLATIE	
SOUND ABSORPTION	ISO 354
ABSORPTION PHONIQUE	0.20 αw
SCHALLABSORPTIONSGRAD	
GELUIDSABSORPTIE	
THERMAL RESISTANCE	ISO 8302
RÉSISTANCE THERMIQUE	0.09 m ² K/W
WÄRMEDURCHLASSWIDERSTAND	
WARMTEDOORLAATWEERSTAND	
FASTNESS TO LIGHT	ISO 105-B02
SOLIDITÉ A LA LUMIÈRE	≥ 5-6
LICHTECHTHEIT	
LICHTECHTHEID	
COLOUR FASTNESS TO WATER	EN ISO 105-E01
SOLIDITÉ À L'EAU	≥ 4-5
WASSERRECHTHEIT	
WATERECHTHEID	
FIRE RESISTANCE	EN 13501-1
COMPORTEMENT AU FEU	Bfl-s1 (if glued) /
BRENNVERHALTEN	Cfl-s1
BRANDGEDRAG	
RUBBING FASTNESS	EN ISO 105-X12
SOLIDITÉ AU FROTTEMENT	≥ 4
REIBECHTHEIT	
WRIJFECHTHEID	
NUMBER OF COLOURS	24
NOMBRES DE COULEURS	
ANZAHL FARBEN	
AANTAL KLEUREN	
WIDTH	EN ISO 3018
LARGEUR	ca. 400 cm
BREITE	
BREEDTE	





TUV NORD
Sonder
Primary Material
Approved to TUV NORD standards


Suitable for Allergic Persons
Wall to wall carpet of allergen-tested material
3.2-2384/05
































EN14041

CE


16

Balta Industries - Kanegemstraat 15 - BE 8700 Tielt

DOP: 1011#IE0ABV


Textile Floor Covering EN1307
Notified body 2401

www.baltamediabank.com



UPEC
moquettes touffées et tissées en lés
<http://evaluation.cstb.fr>


REG. NR
6F7612AC
www.pro-dis.info




prominent ^{AB}



▲ 38



▲ 90




▲ 153



▲ 195




▲ 54



▲ 191



▲ 26



▲ 96



▲ 79



▲ 197

▲ 47



▲ 37




▲ 49



▲ 43




▲ 48



▲ 77




▲ 98



▲ 64




▲ 11




▲ 16



▲ 18



▲ 78



▲ 198

arc edition