

<b>CONSTRUCTION</b>	Tufting 5/64" twist pile
<b>STRUCTURE</b>	Tufté 5/64" frisé
<b>STRUKTUR</b>	Getuftet 5/64" frisé
<b>STRUCTUUR</b>	Getuft 5/64" frizée
<b>PILE MATERIAL</b>	100% PA 6 IMPREL®
<b>COMPOSITION DU VELOURS</b>	
<b>POLMATERIAL</b>	
<b>POOLMATERIAAL</b>	
<b>PRIMARY BACKING</b>	woven PP
<b>SUPPORT</b>	PP tissé
<b>TRÄGERMATERIAL</b>	PP Bändchen
<b>TUFTDOEK</b>	geweven PP
<b>SECONDARY BACKING</b>	Action Back
<b>DOSSIER</b>	
<b>RÜCKEN</b>	
<b>TAPIJTRUG</b>	
<b>PILE WEIGHT</b>	Ca. 1.200 gr/m <sup>2</sup>
<b>POIDS DU VELOURS</b>	
<b>POLEINSATZGEWICHT</b>	
<b>POOLGEWICHT</b>	
<b>TOTAL WEIGHT</b>	Ca. 2.027 gr/m <sup>2</sup>
<b>POIDS TOTAL</b>	
<b>GESAMTGEWICHT</b>	
<b>TOTAAL GEWICHT</b>	
<b>PILE HEIGHT</b>	Ca. 5,6 mm
<b>EPAISSEUR DU VELOURS</b>	
<b>POLHÖHE</b>	
<b>POOLHOOGTE</b>	
<b>TOTAL HEIGHT</b>	Ca. 7,7 mm
<b>EPAISSEUR TOTAL</b>	
<b>GESAMTHÖHE</b>	
<b>TOTALE DIKTE</b>	
<b>TUFT DENSITY</b>	Ca. 278 400/m <sup>2</sup>
<b>NOMBRES DE POINTS</b>	
<b>NOPPENZAHL</b>	
<b>AANTAL PUNTEN</b>	
<b>PILE DENSITY</b>	Ca. 0.168 g/cm <sup>3</sup>
<b>DENSITÉ DU VELOURS</b>	
<b>POLROHDICHTÉ</b>	
<b>POOLDICHTHEID</b>	
<b>CLASSIFICATION</b>	EN 1307
<b>CLASSEMENT</b>	32 - LC4
<b>KLASSIFIKATION</b>	
<b>CLASSIFICATIE</b>	
<b>CASTOR CHAIR SUITABILITY</b>	EN 985
<b>CHAISE À ROULETTES</b>	A: intensive use
<b>STUHLROLLENEIGNUNG</b>	
<b>ROLSTOELGESCHIKTHEID</b>	
<b>STAIR SUITABILITY</b>	EN 1963
<b>ESCALIERS</b>	A: intensive use
<b>TREPPENEIGNUNG</b>	
<b>TRAPPENGESCHIKTHEID</b>	

**PERMANENTLY ANTISTATIC** ISO 6356  
**ANTISTATIC PERMANENT** < 2 kV  
**PERMANENT ANTISTATISCH**  
**PERMANENT ANTISTATISCH**

**IMPACT NOISE RATING** ISO 140-8  
**ISOLATION PHONIQUE** 22 dB ΔLw  
**TRITTSCHALLVERBESSERUNG**  
**GELUIDSISOLATIE**

**SOUND ABSORPTION** ISO 354  
**ABSORPTION PHONIQUE** 0.20 αw  
**SCHALLABSORPTIONSGRAD**

**THERMAL RESISTANCE** ISO 8302  
**RÉSISTANCE THERMIQUE** 0.12 m<sup>2</sup> K/W  
**WÄRMEDURCHLASSWIDERSTAND**  
**WARMTEDOORLAATWEERSTAND**

**FASTNESS TO LIGHT** ISO 105-B02  
**SOLIDITÉ A LA LUMIÈRE** ≥ 5-6  
**LICHTECHTHEIT**  
**LICHTECHTHEID**


**COLOUR FASTNESS TO WATER** EN ISO 105-E01  
**SOLIDITÉ À L'EAU** ≥ 4-5  
**WASSERRECHTHEIT**  
**WATERECHTHEID**

**FIRE RESISTANCE** EN 13501-1  
**COMPORTEMENT AU FEU** Cfl-s1  
**BRENNVERHALTEN** if glued  
**BRANDGEDRAG**

**RUBBING FASTNESS** EN ISO 105-X12  
**SOLIDITÉ AU FROTTEMENT** ≥ 4  
**REIBECHTHEIT**  
**WRIJFECHTHEID**


**NUMBER OF COLOURS** 18  
**NOMBRES DE COULEURS**  
**ANZAHL FARBEN**  
**AANTAL KLEUREN**

**WIDTH** EN ISO 3018  
**LARGEUR** ca. 400 + 500 cm  
**BREITE**  
**BREEDTE**







# evolve <sup>AB</sup>




▲ 23



▲ 93



▲ 92



▲ 15




▲ 39



▲ 33



▲ 38



▲ 95



▲ 65



▲ 43




▲ 49



▲ 94



▲ 98



▲ 72



▲ 77



▲ 79



▲ 97



▲ 99