

# Technische Spezifikation

## TECHNISCHE DATEN ZU DIVINO

Dryback

Click

### PRODUCT INFORMATION

|                          |              |                                     |                                     |
|--------------------------|--------------|-------------------------------------|-------------------------------------|
| Level of use             | EN ISO 10874 | 23 - 33                             | 23 - 33                             |
| Total thickness          | EN ISO 24346 | 2.5 mm                              | 4.5 mm                              |
| Wear layer               | EN ISO 24340 | 0.55 mm                             | 0.55 mm                             |
| Wear Layer PUR treatment |              | Superguard®<br>Embossed in register | Superguard®<br>Embossed in register |
| Total weight g/m²        | EN ISO 23997 | 4105.5                              | 7805.5                              |

### SIZE & PACKING

|               |              |                       |                      |
|---------------|--------------|-----------------------|----------------------|
| Planks        | EN ISO 24342 | 19.6 x 132 cm         | 19.1 x 131.6 cm      |
| Parquetry     | EN ISO 24342 | 15.8 x 63.2 cm        | -                    |
| Box planks    |              | 3.62 m²<br>14 pcs/box | 1.76 m²<br>7 pcs/box |
| Box Parquetry |              | 2.40 m²<br>24 pcs/box | -                    |

### TEST RESULTS

|                                                  |                |                                                    |                                                    |
|--------------------------------------------------|----------------|----------------------------------------------------|----------------------------------------------------|
| Inflammability                                   | EN 13501       | Bfl-S1                                             |                                                    |
| Abrasion group                                   | EN ISO 660-2   | Class T                                            |                                                    |
| Scratch resistance                               | EN 16094       | ≤MSR-A2, ≤MSR-B2                                   |                                                    |
| Squareness                                       | EN ISO 24342   | ≤ 400 mm: ≤ 0.25 mm                                |                                                    |
| Straightness                                     | EN ISO 24342b  | ≤ 400 mm: ≤ 0.35 mm                                |                                                    |
| Slip resistance                                  | EN 13893       | DS                                                 |                                                    |
| Slip restraint                                   | DIN 51130      | R10                                                |                                                    |
| Residual indentation                             | EN ISO 24343-1 | Norm: ≤ 0.10 mm                                    |                                                    |
| Furniture leg resistance                         | EN ISO 16581   | No cracks, no damage                               |                                                    |
| Curling                                          | EN ISO 23999   | ≤ 12 l mm                                          | ≤ 11 l mm                                          |
| Dimensional stability                            | EN ISO 20326   | Norm: ≤ 1 0.25 l %<br>Average result: ≤ 1 0.05 l % | Norm: ≤ 1 0.15 l %<br>Average result: ≤ 1 0.05 l % |
| Thermal resistance R                             | EN 12667       | 0.0100 m² K/W                                      | 0.0159 m² K/W                                      |
| Acoustic insulation                              | EN ISO 717-2   | 4 dB                                               |                                                    |
| Acoustic insulation + Xtrafloor Acoustic Comfort |                | 19 dB                                              |                                                    |
| Castor chair resistance                          | EN ISO 4918    | No damage to wearlayer, no delamination            |                                                    |
| Stain resistance                                 | EN ISO 26987   | Very good                                          |                                                    |
| Light fastness                                   | EN ISO 105-B02 | ≥ 6                                                |                                                    |
| Underfloor heating and cooling                   | EN 12524       | Suitable, max 27°C                                 |                                                    |
| Maximum allowed ambient and surface temperature  |                | 45° C                                              |                                                    |
| Warranty (year)                                  |                | 20 Residential - 10 Commercial                     |                                                    |

Die Garantie deckt Herstellungsfehler und vorzeitigen Verschleiß bei normalem Gebrauch ab.

|                                                                                     |    |                          |                  |                                                                          |                          |                           |
|-------------------------------------------------------------------------------------|----|--------------------------|------------------|--------------------------------------------------------------------------|--------------------------|---------------------------|
|  | 13 | EN14041:2004/<br>AC:2006 | Reaction to fire | PCP                                                                      | Formaldehyde<br>emission | Slip resistance           |
|                                                                                     |    |                          | Bfl-s1           | < 5PPM                                                                   | E1                       | DS                        |
|                                                                                     |    |                          | Water-tightness  | Electrical<br>resistance                                                 | Thermal<br>resistance    | Antistatic<br>performance |
|                                                                                     |    |                          | NA               | NPD                                                                      | NPD                      | NPD                       |
| IVC bv - Nijverheidslaan 29<br>B-8580 Avelgem, Belgium<br>0032/56/67/5211           |    |                          |                  | LVT FLEX DB / 2 mm / 0,55 mm<br>for indoor use according to EN ISO 10874 |                          |                           |
| DOP - LVT                                                                           |    | ivcgroup.com             |                  |                                                                          |                          |                           |

|                                                                                     |    |                          |                                                                            |                          |                          |                           |  |
|-------------------------------------------------------------------------------------|----|--------------------------|----------------------------------------------------------------------------|--------------------------|--------------------------|---------------------------|--|
|  | 13 | EN14041:2004/<br>AC:2006 | Reaction to fire                                                           | PCP                      | Formaldehyde<br>emission | Slip resistance           |  |
|                                                                                     |    |                          | Bfl-s1                                                                     | < 5PPM                   | E1                       | DS                        |  |
|                                                                                     |    |                          | Water-tightness                                                            | Electrical<br>resistance | Thermal<br>resistance    | Antistatic<br>performance |  |
|                                                                                     |    |                          | NA                                                                         | NPD                      | NPD                      | NPD                       |  |
| IVC bv - Nijverheidslaan 29<br>B-8580 Avelgem, Belgium<br>0032/56/67/5211           |    |                          | LVT FLEX CL / 4,5 mm / 0,55 mm<br>for indoor use according to EN ISO 10874 |                          |                          |                           |  |
| DOP - LVT                                                                           |    | ivcgroup.com             |                                                                            |                          |                          |                           |  |

