

Technische Spezifikation

TECHNISCHE DATEN ZU PRIMERO

Dryback

Click

PRODUCT INFORMATION

Level of use	EN ISO 10874	23 - 31	23 - 31
Total thickness	EN ISO 24346	2 mm	4.5 mm
Wear layer	EN ISO 24340	0.3 mm	0.3 mm
Wear Layer PUR treatment		Superguard®	Superguard®
Total weight g/m²	EN ISO 23997	3328	7953

SIZE & PACKING

Planks	EN ISO 24342	16.3 x 98.8 cm	19.1 x 131.6 cm
Tiles	EN ISO 24342	32.9 x 65.9 cm	32.4 x 65.5 cm
Box planks		3.87 m² 24 pcs/box	1.76 m² 7 pcs/box
Box tiles		3.90 m² 18 pcs/box	1.49 m² 7 pcs/box

TEST RESULTS

Inflammability	EN 13501	Bfl-S1
Abrasion group	EN ISO 660-2	Class T
Scratch resistance	EN 16094	≤MSR-A2, ≤MSR-B2
Squareness	EN ISO 24342	≤ 0.20 mm
Straightness	EN ISO 24342a	≤ 0.35 mm
Slip resistance	EN 13893	DS
Slip restraint	DIN 51130	R10
Residual indentation	EN ISO 24343-1	≤ 0.10 mm
Furniture leg resistance	EN ISO 16581	No cracks, no damage
Curling	EN ISO 23999	≤ 12 l mm ≤ 1 l mm
Dimensional stability	EN ISO 20326	Norm: ≤ 1.025 l % Average result: ≤ 0.10% Norm: ≤ 1.015 l % Average result: ≤ 0.10%
Thermal resistance R	EN 12667	0.04 m² K/W 0.04 m² K/W
Acoustic insulation	EN ISO 717-2	4 dB
Acoustic insulation + Xtrafloor Acoustic Comfort		19 dB
Castor chair resistance	EN ISO 4918	No damage to wearlayer, no delamination
Stain resistance	EN ISO 26987	Very good
Light fastness	EN ISO 105-B02	≥ 6
Underfloor heating and cooling	EN 12524	Suitable, max 27°C
Warranty (year)		12 Residential - 5 Commercial

Die Garantie deckt Herstellungsfehler und vorzeitigen Verschleiß bei normalem Gebrauch ab.

	17	EN14041:2004/ AC:2006	Reaction to fire	PCP	Formaldehyde emission	Slip resistance		
			Bfl-s1	< 5PPM	E1	DS		
			Water-tightness	Electrical resistance	Thermal resistance	Antistatic performance		
			NA	NPD	NPD	NPD		
IVC bv - Nijverheidslaan 29 B-8580 Avelgem, Belgium 0032/56/67/5211			LVT FLEX DB / 2 mm / 0.3 mm for indoor use according to EN ISO 10874					
DOP - LVT			ivcgroup.com					

	11	EN14041:2004/ AC:2006	Reaction to fire	PCP	Formaldehyde emission	Slip resistance		
			Bfl-s1	< 5PPM	E1	DS		
			Water-tightness	Electrical resistance	Thermal resistance	Antistatic performance		
			NA	NPD	NPD	NPD		
IVC bv - Nijverheidslaan 29 B-8580 Avelgem, Belgium 0032/56/67/5211			LVT FLEX CL / 4.5 mm / 0.3 mm for indoor use according to EN ISO 10874					
DOP - LVT			ivcgroup.com					

