

marble fusion WFB

CONSTRUCTION ituft 1/12" loop tipsheared
STRUCTURE ituft 1/12" bouclé tipsheared
STRUKTUR ituft 1/12" Tipsheared-Schlinge
STRUCTUUR ituft 1/12" lussenpool tipsheared

PILE MATERIAL 100% PA 6 IMPREL® Solution Dyed
COMPOSITION DU VELOURS
POLMATERIAL
POOLMATERIAAL

PRIMARY BACKING Non woven PES
SUPPORT PES non tissé
TRÄGERMATERIAL PES Vlies
TUFTDOEK PES Vilt

SECONDARY BACKING Twinback
DOSSIER
RÜCKEN
TAPIJTRUG

PILE WEIGHT Ca. 800 gr/m²
POIDS DU VELOURS
POLEINSATZGEWICHT
POOLGEWICHT

TOTAL WEIGHT Ca. 2.400 gr/m²
POIDS TOTAL
GESAMTGEWICHT
TOTAAL GEWICHT

PILE HEIGHT Ca. 3,6-5,2 mm
EPAISSEUR DU VELOURS
POLHÖHE
POOLHOOGTE

TOTAL HEIGHT Ca. 7,7-9,3 mm
EPAISSEUR TOTAL
GESAMTHÖHE
TOTALE DIKTE

TUFT DENSITY Ca. 282 000/m²
NOMBRES DE POINTS
NOPPENZAHL
AANTAL PUNTEN

PILE DENSITY Ca. 0,122 g/cm³
DENSITÉ DU VELOURS
POLROHDICHTE
POOLDICHTHEID

CLASSIFICATION EN 1307
CLASSEMENT 32 - LC2
KLASSIFIKATION
CLASSIFICATIE

CASTOR CHAIR SUITABILITY EN 985
CHAISE À ROULETTES A: intensive use
STUHLROLLENEIGNUNG
ROLSTOELGESCHIKTHEID

STAIR SUITABILITY EN 1963
ESCALIERS A: intensive use
TREPPENEIGNUNG
TRAPPENGESCHIKTHEID

PERMANENTLY ANTISTATIC ISO 6356
ANTISTATIQUE PERMANENT ≤ 2 kV
PERMANENT ANTISTATISCH
PERMANENT ANTISTATISCH

IMPACT NOISE RATING ISO 140-8
ISOLATION PHONIQUE 26 dB ΔLw
TRITTSCHALLVERBESSERUNG
GELUIDSISOLATIE

SOUND ABSORPTION ISO 354
ABSORPTION PHONIQUE 0,25 αw
SCHALLABSORPTIONSGRAD

THERMAL RESISTANCE ISO 8302
RÉSISTANCE THERMIQUE 0,11 m² K/W
WÄRMEDURCHLASSWIDERSTAND
WARMTEDOORLAATWEERSTAND

FASTNESS TO LIGHT ISO 105-B02
SOLIDITÉ A LA LUMIÈRE ≥ 7
LICHTECHTHEIT
LICHTECHTHEID


COLOUR FASTNESS TO WATER EN ISO 105-E01
SOLIDITÉ À L'EAU ≥ 4-5
WASSERECHTHEIT
WATERECHTHEID

FIRE RESISTANCE EN 13501-1
COMPORTEMENT AU FEU Cfl-s1
BRENNVERHALTEN
BRANDGEDRAG

RUBBING FASTNESS EN ISO 105-X12
SOLIDITÉ AU FROTTEMENT ≥ 4
REIBECHTHEIT
WRIJFECHTHEID

NUMBER OF COLOURS 9
NOMBRES DE COULEURS
ANZAHL FARBEN
AANTAL KLEUREN

WIDTH EN ISO 3018
LARGEUR ca. 400 cm
BREITE
BREEDTE



www.pro-dis.info



EN14041
CE
21
Balta Industries - Kanegem- straat 15 - BE 8700 Tielt DOP: 1011#IE0ACL
Textile Floor Covering EN1307 Notified body 2401
www.baltamediabank.com

marble fusion WFB




↔ ca.199 cm x ↕ ca.424 cm




▲ 35




▲ 47




▲ 96



▲ 95




▲ 90



▲ 27



▲ 77



▲ 97



▲ 98

 arc edition